Xtend

Active Annotations

java.beans

Class PropertyChangeSupport

java.lang.Object

java.beans.PropertyChangeSupport

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

SwingPropertyChangeSupport

```
public class PropertyChangeSupport
extends Object
implements Serializable
```

This is a utility class that can be used by beans that support bound properties. It manages a list of listeners and dispatches [PropertyChangeEvent](#)s to them. You can use an instance of this class as a member field of your bean and delegate these types of work to it. The [PropertyChangeListener](#) can be registered for all properties or for a property specified by name.

Here is an example of `PropertyChangeSupport` usage that follows the rules and recommendations laid out in the [JavaBeans™](#) specification:

```
public class MyBean {
    private final PropertyChangeSupport pcs = new PropertyChangeSupport(this);

    public void addPropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.addPropertyChangeListener(listener);
    }

    public void removePropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.removePropertyChangeListener(listener);
    }

    private String value;

    public String getValue() {
        return this.value;
    }

    public void setValue(String newValue) {
        String oldValue = this.value;
        this.value = newValue;
        this.pcs.firePropertyChange("value", oldValue, newValue);
    }
}
```

Class PropertyChangeSupport

java.lang.Object
java.beans.PropertyChangeSupport

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

SwingPropertyChangeSupport

```
public class PropertyChangeSupport
extends Object
implements Serializable
```

This is a utility class that can be used by beans that support bound properties. It manages a list of listeners and dispatches [PropertyChangeEvent](#)s to them. You can use an instance of this class as a member field of your bean and delegate these types of work to it. The [PropertyChangeListener](#) can be registered for all properties or for a property specified by name.

Here is an example of PropertyChangeSupport usage that follows the rules and recommendations laid out in the JavaBeans™ specification:

```
public class MyBean {
    private final PropertyChangeSupport pcs = new PropertyChangeSupport(this);

    public void addPropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.addPropertyChangeListener(listener);
    }

    public void removePropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.removePropertyChangeListener(listener);
    }

    private String value;

    public String getValue() {
        return this.value;
    }

    public void setValue(String newValue) {
        String oldValue = this.value;
        this.value = newValue;
        this.pcs.firePropertyChange("value", oldValue, newValue);
    }

    [...]
}
```

A PropertyChangeSupport instance is thread-safe.

Class PropertyChangeSupport

java.lang.Object
java.beans.PropertyChangeSupport

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

SwingPropertyChangeSupport

```
public class PropertyChangeSupport
extends Object
implements Serializable
```

This is a utility class that can be used by beans that support bound properties. It manages a list of listeners and dispatches `PropertyChangeEvent`s to them. You can use an instance of this class as a member field of your bean and delegate these types of work to it. The `PropertyChangeListener` can be registered for all properties or for a property specified by name.

Here is an example of `PropertyChangeSupport` usage that follows the rules and recommendations laid out in the JavaBeans™ specification:

```
public class MyBean {
    private final PropertyChangeSupport pcs = new PropertyChangeSupport(this);

    public void addPropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.addPropertyChangeListener(listener);
    }

    public void removePropertyChangeListener(PropertyChangeListener listener) {
        this.pcs.removePropertyChangeListener(listener);
    }

    private String value;

    public String getValue() {
        return this.value;
    }

    public void setValue(String newValue) {
        String oldValue = this.value;
        this.value = newValue;
        this.pcs.firePropertyChange("value", oldValue, newValue);
    }

    [...]
}
```

A `PropertyChangeSupport` instance is thread-safe.

```
class MyBean {  
    String value  
}
```

```
@Observable  
class MyBean {  
    String value  
}
```

```
package observable

import org.eclipse.xtend.lib.macros.AbstractClassProcessor
import org.eclipse.xtend.lib.macros.Active
import org.eclipse.xtend.lib.macros.declaration.MutableClassDeclaration
import org.eclipse.xtend.lib.macros.TransformationContext
```

```
@Active(typeof(ObservableProcessor))
```

```
annotation Observable {
}
```

```
class ObservableProcessor extends AbstractClassProcessor {
```

```
    override doTransform(MutableClassDeclaration annotatedClass, extension TransformationContext context) {
```

```
    }
```

```
}
```

```
package observable

import org.eclipse.xtend.lib.macro.AbstractClassProcessor
import org.eclipse.xtend.lib.macro.Active
import org.eclipse.xtend.lib.macro.declaration.MutableClassDeclaration
import org.eclipse.xtend.lib.macro.TransformationContext
```

```
@Active(typeof(ObservableProcessor))
```

```
annotation Observable {
}
```

```
class ObservableProcessor extends AbstractClassProcessor {
```

```
    override doTransform(MutableClassDeclaration annotatedClass, extension TransformationContext context) {
```

```
        for (f : annotatedClass.declaredFields) {
```

```
            val fieldName = f.simpleName
```

```
            val fieldType = f.type
```

```
            annotatedClass.addMethod('get'+fieldName.toFirstUpper) [
```

```
                returnType = fieldType
```

```
                body = ['''return this.«fieldName»;''']
```

```
            ]
```

```
            annotatedClass.addMethod('set'+fieldName.toFirstUpper) [
```

```
                addParameter(fieldName, fieldType)
```

```
                body = ['''
```

```
                    «fieldType» _oldValue = this.«fieldName»;
```

```
                    this.«fieldName» = «fieldName»;
```

```
                    _propertyChangeSupport.firePropertyChange("«fieldName»", _oldValue, «fieldName»);
```

```
                ''']
```

```
            ]
```

```
        }
```

```
    }
```

```
}
```

```
package observable
```

```
import org.eclipse.xtend.lib.macro.AbstractClassProcessor  
import org.eclipse.xtend.lib.macro.Active  
import org.eclipse.xtend.lib.macro.declaration.MutableClassDeclaration  
import org.eclipse.xtend.lib.macro.TransformationContext  
import java.beans.PropertyChangeSupport
```

```
@Active(typeof(ObservableProcessor))
```

```
annotation Observable {  
}
```

```
class ObservableProcessor extends AbstractClassProcessor {
```

```
    override doTransform(MutableClassDeclaration annotatedClass, extension TransformationContext context) {
```

```
        for (f : annotatedClass.declaredFields) {
```

```
            val fieldName = f.simpleName
```

```
            val fieldType = f.type
```

```
            annotatedClass.addMethod('get'+fieldName.toFirstUpper) [
```

```
                returnType = fieldType
```

```
                body = ['''return this.«fieldName»;''']
```

```
            ]
```

```
            annotatedClass.addMethod('set'+fieldName.toFirstUpper) [
```

```
                addParameter(fieldName, fieldType)
```

```
                body = ['''
```

```
                    «fieldType» _oldValue = this.«fieldName»;
```

```
                    this.«fieldName» = «fieldName»;
```

```
                    _propertyChangeSupport.firePropertyChange("«fieldName»", _oldValue, «fieldName»);
```

```
                ''']
```

```
            ]
```

```
        }
```

```
        val changeSupportType = typeof(PropertyChangeSupport).newTypeReference
```

```
        annotatedClass.addField('_propertyChangeSupport') [
```

```
            type = changeSupportType
```

```
            initializer = ['''new «toJavaCode(changeSupportType)»(this)''']
```

```
        ]|
```

```
    }
```

```
Observable.xtend
@Active(typeOf(observableProcessor))
annotation Observable {
}

class ObservableProcessor extends AbstractClassProcessor {

  override doTransform(MutableClassDeclaration annotatedClass, extension TransformationContext context) {
    for (f : annotatedClass.declaredFields) {
      val fieldName = f.simpleName
      val fieldType = f.type

      annotatedClass.addMethod('get'+fieldName.toFirstUpper) [
        returnType = fieldType
        body = ['return this.«fieldName»;']
      ]

      annotatedClass.addMethod('set'+fieldName.toFirstUpper) [
        addParameter(fieldName, fieldType)
        body = ['''
          «fieldType» _oldValue = this.«fieldName»;
          this.«fieldName» = «fieldName»;
          _propertyChangeSupport.firePropertyChange("«fieldName»", _oldValue, «fieldName»);
        ''']
      ]
    }

    val changeSupportType = typeOf(PropertyChangeSupport).newTypeReference
    annotatedClass.addField('_propertyChangeSupport') [
      type = changeSupportType
      initializer = ['new «toJavaCode(changeSupportType)»(this)']
    ]

    val propertyChangeListenerType = typeOf(PropertyChangeListener).newTypeReference
    annotatedClass.addMethod('addPropertyChangeListener') [
      addParameter('listener', propertyChangeListenerType)
      body = ['this._propertyChangeSupport.addPropertyChangeListener(listener);']
    ]
    annotatedClass.addMethod('removePropertyChangeListener') [
      addParameter('listener', propertyChangeListenerType)
      body = ['this._propertyChangeSupport.removePropertyChangeListener(listener);']
    ]
  }
}

Writable Insert 4
```

Package Explorer

- observable
 - Xtend Library
 - xtend-gen
 - src
 - observable
 - Observable.xtend
 - Person.xtend
 - JRE System Library [JavaSE-1.6]

```

package observable
class Person {
    String firstName
    String lastName
    def getFullName() {
        firstName + ' ' + lastName
    }
}

```

Outline

- observable
 - Person
 - firstName : String
 - lastName : String
 - getFullName() : String

Problems @ Javadoc Declaration

0 items

Description	Resource	Path	Location	Type

IDE interface showing the development of an Xtend class. The main editor displays the following code:

```

package observable

@Observable
class Person {
    String firstName
    String lastName
    def getFullName() {
        firstName + ' ' + lastName
    }
}

```

The Package Explorer on the left shows the project structure:

- observable
 - Xtend Library
 - xtend-gen
 - src
 - observable
 - Observable.xtend
 - Person.xtend
- JRE System Library [JavaSE-1.6]

The Outline on the right shows the class hierarchy:

- observable
 - Person
 - firstName : String
 - lastName : String
 - getFullName() : String
 - getFirstName() : String
 - setFirstName(String)
 - getLastName() : String
 - setLastName(String)
 - _propertyChangeSup
 - addPropertyChangeL
 - removePropertyChan

The Problems view at the bottom shows 0 items. The status bar at the bottom indicates the cursor is at line 3, column 12.

DEMO